



Fibre optic patch panel OV-AT, 19"/2U, without front plate,
extractable or with telescopic slides, depth-adjustable mounting

DESCRIPTION

For the termination of fibre optic cables (breakout, loose tube) - maximum of 192 fibres.
Applicable with a wide range of front plates / connector systems
(see OV-A / OV-AT 2U accessories).

SCOPE OF DELIVERY

Box, strain relief with M25 (2U) cable gland,
splice tray holder and adhesive fibre fixation (3 pcs.)

Please order the front plate separately.

GENERAL PROPERTIES

Housing:	metallic, extractable drawer (OV-A) or drawer with telescopic slides (OV-AT), both with locking mechanism
Rack mounting:	depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour mounting brackets (variants):	similar to RAL 7035 or stainless steel
Imprint:	numbers (silk screen printing) on frontplate (to be ordered separately)
Capacity:	up to 192 fibres
Strain relief:	with cable tie and screwed cable gland or cable distributor
Cable entry:	rear left and right (the openings are covered with a blind cover and a straight cable entry plate with M20 and M25 slotted holes - Article No. 417561)
Dimensions:	19"/2U, depth 254 mm
Connector system	
Adapter:	ST, FC, SCD, SC, LSH, LCD (dependent on front plate)

VERSIONS

Article Number	Product	Colour (similar to)	Note
416960	OV-A extractable 2U	light grey, RAL 7035	without front plate
416965	OV-AT telescopic 2U	light grey, RAL 7035	without front plate
416977	OV-AT telescopic 2U	stainless steel	without front plate
416959	Telescopic slides for upgrading OV-A to OV-AT		
418098	Label for OV-A and OV-AT, aluminium, length 420 mm		