



Fibre optic patch panel OV-AT, 19"/1U, without front plate,  
with telescopic slides, depth-adjustable mounting

---

## DESCRIPTION

For the termination of fibre optic cables (breakout, loose tube) - maximum of 96 fibres.  
Applicable with a wide range of front plates / connector systems (see OV-AT / OV-S 1U accessories).

---

## SCOPE OF DELIVERY

Box, strain relief with M20 (1U) cable gland, splice tray holder and adhesive fibre fixation (3 pcs.)

Please order the front plate separately.

---

## GENERAL PROPERTIES

Housing:	metallic, with telescopic slides and locking mechanism
Rack mounting:	depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour of mounting brackets (variants):	similar to RAL 7035, similar to RAL 9005 or stainless steel
Imprint:	numbers (silk screen printing) on front plate (to be ordered separately)
Capacity:	up to 96 fibres
Strain relief:	with cable tie and screwed cable gland or cable distributor
Cable entry:	rear left and right (the openings are covered with a blind cover and a straight cable entry plate with M20 and M25 slotted holes - Article No. 416994)
Dimensions:	19"/1U, depth 254 mm
<b>Connector system</b>	
Adapter:	ST, FC, SCD, SC, LSH, LCD (dependent on front plate)

---

## VERSIONS

Article Number	Product	Colour (similar to)	Note
416964	OV-AT telescopic 1U	light grey, RAL 7035	without front plate
on request	OV-AT telescopic 1U	black, RAL 9005	without front plate
416975	OV-AT telescopic 1U	stainless steel	without front plate
1405304	Label for OV-AT, self-adhesive, length 420 mm		