

FO patch panel OV-S

19"/1U, unloaded



Fibre optic patch panel OV-S, 19"/1U, without front plate, extractable, depth-adjustable mounting

DESCRIPTION

For the termination of fibre optic cables (breakout, loose tube) - maximum of 96 fibres.
Applicable with a wide range of front plates / connector systems (see OV-S / OV-AT 1U accessories).

SCOPE OF DELIVERY

Box, with straight cable entry plates, splice tray holder.

Please order the front plate separately.

GENERAL PROPERTIES

Housing: metallic, extractable drawer with locking mechanism
Rack mounting: depth-adjustable mounting of box (5 steps, maximum 50 mm) due to the adjustable 19" mounting brackets
Colour: similar to RAL 7035, similar to RAL 9005 and stainless steel
mounting brackets (variants):
Capacity: up to 96 fibres
Strain relief: with cable tie and screwed cable gland or cable distributor
Cable entry: rear left and right (two big openings, covered with straight cable entry plates: Article No. 415308 with pre-stamped cable entries M20 and M25 and Article No. 418650 with pre-stamped cable entries 2x M15, 1x M20 – these pre-stamped holes can be opened as necessary)
Dimensions: 19"/1U, depth 300 mm
Option: An additional element (folding mechanism) allows the drawer to be hinged down at a 45 degree angle (tool-less assembly)

Connector system

Adapter: ST, FC, SCD, SC, LSH, LCD (dependent on front plate)

VERSIONS

Article Number	Product	Colour (similar to)	Note
415201	OV-S extractable 1U	light grey, RAL 7035	without front plate
415203	OV-S extractable 1U	black, RAL 9005	without front plate
415204	OV-S extractable 1U	stainless steel	without front plate
415245	Folding mechanism for OV-S 1U		